

General Description

PROMASTOP®-S and PROMASTOP®-L fire stopping is a graphite-based pillow, which enables quick and easy, dust-free installation. Pillows that have previously been installed can be reused provided they have not been subjected to fire.

Field Of Application

PROMASTOP®-S and PROMASTOP®-L is a fire stopping pillow for walls and floors. It is designed for use with cables, cable trays and plastic pipes to seal against the spread of fire.

System Advantage / Customer Benefit

- Temporary penetration during construction and easy retro-fitting;
- Permanent penetration at base of walls (smoke);
- Dust proof, suitable for computer and server centres.

General Technical Properties

Colour	light grey
Consistency	compact
Density	230 – 430 g/l
Solid content	100 %
Reaction to fire	B1, slowly combustible
Expansion ratio	minimum 1:2.5 (30 mins. / 600 °C)
Expansion temperature	approx. 150 °C
Volume	PROMASTOP®-L approx. 2 l PROMASTOP®-S approx. 1 l
Dimensions PROMASTOP®-L PROMASTOP®-S	approx. 320 x 200 mm approx. 320 x 100 mm

Test Certificate / Approval

- EN 1366-3 (cable/cable bundles, pipes), EN 13501-2/classification reports
- ÖNORM B 3807
- ASTM/UL

Packaging

- PROMASTOP®-S – 10 pieces per carton
 - PROMASTOP®-L – 5 pieces per carton
- Subject to change!



Storage Requirements

- Store in cool and dry conditions

Safety Instructions

- Keep out of reach of children
- Avoid contact with food or beverages
- Please refer to the safety data sheet for additional advice